

TABLE OF CONTENTS

Title	Page No.
Certificate	i
Acknowledgment	ii
Declaration of Originality of Research Work and Thesis by the Scholar and Supervisor	iii
Plagiarism Verification Certificate	iv
Abstract	v
Table of Contents	viii
List of Figures	xiii
List of Tables	xviii
List of Abbreviations	xx
Chapter 1	1-19
1. Introduction	1
1.1 Process Parameters	3
1.2 Machinability Factors	4
1.2.1 Effect of Cutting Parameters on Surface Quality	4
1.3 Duplex Stainless Steel	5
1.4 Machining	6
1.4.1 Chip Formation During Machining	6
1.4.2 Surface Roughness	8
1.4.4 Tool Wear	9
1.4.5 Hole Dimensional Accuracy	9
1.5 Cutting Tool Material	10
1.6 Difficulties in Machining of Duplex Stainless Steel	11
1.7 Environmental-Friendly Machining	11

Title	Page No.
1.7.1 Classification of Environmental Friendly Machining	12
1.7.1.1 Dry Machining	13
1.7.1.2 Minimum Quantity of Lubrication (MQL)	13
1.7.1.3 MQL-Nano Particles	14
1.7.1.4 Cryogenic Machining	15
1.7.1.5 High-Pressure Cooling Machining	15
1.8 Optimization Tools and Techniques	17
1.9 Organization of the Thesis	17
1.10 Plan of Action	19
Chapter 2	20-55
2. Literature Review	20
2.1 Literature Review	20
2.2 Critical Literature Review	51
2.3 Summary of Literature	53
2.4 Research Gaps	54
2.5 Research Objectives	55
Chapter 3	56-68
3. Research Methodology	56
3.1 Taguchi Method	57
3.1.1 Introduction	57
3.1.2 Orthogonal Array (OA)	57
3.1.3 Taguchi Design in Minitab	58
3.1.4 Analysis of Variance (ANOVA)	58
3.2 Response Surface Method	61
3.3 Genetic Algorithm (GA)	62
3.4 Artificial Neural Network (ANN)	64

Title		Page No.
3.5	Fuzzy Logic System (FLS)	65
3.5.1	Introduction	65
3.5.2	Operation of Fuzzy Logic System	65
3.5.3	Membership Function	66
3.6	Adaptive Neural Fuzzy Interface System (ANFIS)	67
3.7	Technique for Order Preference by Similarity to Ideal Solution	68
Chapter 4		69-89
4.	Experimental Work	69
4.1	Experimental Setup	69
4.1.1	CNC Machine	69
4.1.2	Workpiece Material	70
4.1.3	Cutting Tool and Holder	71
4.1.3.1	Cutting Tool	71
4.1.3.2	Tool Holder	71
4.1.4	Minimum Quantity of Lubrication (MQL)	72
4.1.5	Liquid Carbon Dioxide (LCO ₂)	75
4.2	Measuring Instrument	76
4.2.1	Surface Roughness Tester	76
4.2.2	Coordinate Measuring Machine (CMM)	77
4.2.3	Visible Tool Wear Analysis	78
4.3	Experimental Plan	79
4.3.1	Experimental Investigation Under Dry and Wet Conditions	79
4.3.1.1	Cutting Parameters and Response Variables	79
4.3.1.2	Design of Experiment (DOE)	80

	Title	Page No.
4.3.2	Experimental Investigation Under Dry, MQL, and LCO ₂ Conditions	81
4.3.2.1	Cutting Parameters and Response Variables	81
4.3.2.2	Design of Experiment (DOE)	82
4.3.3	Experimental Investigation Under Hybrid MQL-LCO ₂	83
4.3.3.1	Cutting Parameters and Response Variables	84
4.3.3.2	Design of Experiment (DOE)	85
4.4	Measured Responses	86
4.4.1	Surface Roughness	86
4.4.2	Hole Deviation	87
4.4.3	Cylindricity Error	88
4.4.4	Circularity Error	89
Chapter 5		90-175
5.	Results and Discussion	90
5.1	Experimental Investigation Under Dry and Wet Conditions	90
5.1.1	Experimental Results	90
5.1.2	Variation of Surface Roughness with Input Parameters	91
5.1.3	Interaction Plot of Ra Under Dry and Wet Conditions	92
5.1.4	Response Table	93
5.1.5	ANOVA Analysis	94
5.1.6	Regression Analysis	95
5.1.7	Contour Plot for Ra	96
5.1.8	Confirmation Test	97
5.2	Experimental Investigation Under Dry, MQL, and LCO₂ Conditions	98
5.2.1	Experimental Results	99
5.2.2	Variation of Ra with Input Parameters	100

		Title	Page No.
5.2.3		Variation Hole Deviation with Input Parameters	101
5.2.4		Interaction Plot	102
	5.2.4.1	Interaction Plot for Ra	102
	5.2.4.2	Interaction Plot for Hole Deviation	103
5.2.5		Selection of Optimum Parameters	104
	5.2.5.1	Response Table of Ra	104
	5.2.5.2	Response Table of Hole Deviation	106
5.2.6		ANOVA Analysis for Ra and Hole Deviation	107
5.2.7		Regression Analysis	110
5.2.8		Confirmation Test	115
5.2.9		Implemented Genetic Algorithm (GA)	117
	5.2.9.1	Working Principle of GA	118
	5.2.9.2	Fitness Function	118
	5.2.9.3	Generation of the Initial Population	119
	5.2.9.4	Parameters Setting	119
	5.2.9.5	Determine the Optimal Combination for Ra	119
	5.2.9.6	Determine the Optimal Combination for Hole Deviation	120
5.2.10		Tool Wear Analysis	120
5.3		Experimental Investigation Under Hybrid MQL-LCO₂ Condition	122
5.3.1		Experimental Results	122
5.3.2		Variation of Input Parameters on Responses	123
	5.3.2.1	Variation of Hole Deviation	123
	5.3.2.2	Variation of Cylindricity Error	124
	5.3.2.3	Variation of Circularity Error	124
5.3.3		Interaction Plot	125

	Title	Page No.
5.3.3.1	Interaction Plot for Hole Deviation	125
5.3.3.2	Interaction Plot for Cylindricity Error	126
5.3.3.3	Interaction Plot for Circularity Error	128
5.3.4	ANOVA Analysis	129
5.3.4.1	ANOVA Analysis for Hole Deviation	129
5.3.4.2	ANOVA Analysis for Cylindricity Error	131
5.3.4.3	ANOVA Analysis for Circularity Error	132
5.3.5	Contour Plot	135
5.3.6	Modeling of Process Parameters	137
5.3.6.1	Artificial Neural Network (ANN)	137
5.3.6.2	Response Surface Method (RSM)	140
	5.3.6.2.1 Surface Plot for Hole Deviation	141
	5.3.6.2.2 Surface Plot for Cylindricity Error	142
	5.3.6.2.3 Surface Plot for Circularity Error	143
5.3.6.3	Fuzzy Logic System (FLS)	143
	5.3.6.3.1 Membership Function	144
	5.3.6.3.2 Rules	147
	5.3.6.3.3 3-D Surface Plot	149
5.3.6.4	Modeling Through ANFIS	153
	5.3.6.4.1 Prediction of Hole Deviation by ANFIS	154
	5.3.6.4.2 Prediction of Cylindricity Error by ANFIS	156
	5.3.6.4.3 Prediction of Circularity Error by ANFIS	157
5.3.7	Comparison of Experimental Value to Predicated Value	159
5.3.7.1	Comparison of Experimental Value to Fuzzy, RSM, ANN, and ANFIS Model Value for Hole Deviation	159

Title		Page No.
5.3.7.2	Comparison of Experimental Value to Fuzzy, RSM, ANN, and ANFIS Model Value for Circularity Error	162
5.3.7.3	Comparison of Experimental Value to Fuzzy value, RSM Model Value, ANN, and ANFIS Value for circularity Error	165
5.3.8	TOPSIS	169
Chapter 6		169-172
6.	Conclusion & Future Scope	175
6.1	General Conclusions	175
6.2	Future Scope of the Research Work	177
6.3	Summary	178
References		179-191
List of Publications		xxi-xxiii
CV		xxiv-xxix