



References

REFERENCES

- Abbas, A. T., Gupta, M. K., Soliman, M. S., Mia, M., Hegab, H., Luqman, M., & Pimenov, D. Y. (2019). Sustainability assessment associated with surface roughness and power consumption characteristics in nanofluid MQL-assisted turning of AISI 1045 steel. *The International Journal of Advanced Manufacturing Technology*, 105, 1311-1327.
- Adalarasan, R., Santhanakumar, M., & Rajmohan, M. (2015). Application of Grey Taguchi-based response surface methodology (GT-RSM) for optimizing the plasma arc cutting parameters of 304L stainless steel. *The International Journal of Advanced Manufacturing Technology*, 78(5), 1161-1170.
- Airao, J., & Nirala, C. K. (2022). Machinability of Ti-6Al-4V and Nimonic-90 in ultrasonic-assisted turning under sustainable cutting fluid. *Materials Today: Proceedings*, 62, 7396-7400.
- Airao, J., Khanna, N., & Nirala, C. K. (2022). Tool wear reduction in machining Inconel 718 by using novel sustainable cryo-lubrication techniques. *Tribology International*, 175, 107813.
- Al-Ghamdi, K. A., Iqbal, A., & Hussain, G. (2015). Machinability comparison of AISI 4340 and Ti-6Al-4V under cryogenic and hybrid cooling environments: A knowledge engineering approach. *Proceedings of the Institution of Mechanical Engineers, Part B: Journal of Engineering Manufacture*, 229(12), 2144-2164.
- AlRassas, A. M., Al-qaness, M. A., Ewees, A. A., Ren, S., Abd Elaziz, M., Damaševičius, R., & Krilavičius, T. (2021). Optimized ANFIS model using Aquila Optimizer for oil production forecasting. *Processes*, 9(7), 1194.
- Amini, S., Baraheni, M., & Esmaili, S. J. (2019). Experimental comparison of MO40 steel surface grinding performance under different cooling techniques. *International Journal of Lightweight Materials and Manufacture*, 2(4), 330-337.

- An, Q., Cai, C., Zou, F., Liang, X., & Chen, M. (2020). Tool wear and machined surface characteristics in side milling Ti6Al4V under dry and supercritical CO₂ with MQL conditions. *Tribology International*, 151, 106511.
- Ankalagi, S., Gaitonde, V. N., & Petkar, P. (2017). Experimental studies on hole quality in drilling of SA182 steel. *Materials today: proceedings*, 4(10), 11201-11209.
- Aslantas, K., Cicek, A. D. E. M., Uzun, I., Percin, M., & Hopa, H. E. (2016). Performance evaluation of a hybrid cooling–lubrication system in micro-milling of Ti6Al4V alloy. *Procedia CIRP*, 46, 492-495.
- Ayed, Y., Germain, G., Melsio, A. P., Kowalewski, P., & Locufier, D. (2017). Impact of supply conditions of liquid nitrogen on tool wear and surface integrity when machining the Ti-6Al-4V titanium alloy. *The International Journal of Advanced Manufacturing Technology*, 93(1), 1199-1206.
- Bagherzadeh, A., & Budak, E. (2018). Investigation of machinability in turning of difficult-to-cut materials using a new cryogenic cooling approach. *Tribology International*, 119, 510-520.
- Boy, M. (2022). Performance evaluation of coated ceramic tools in nano-MQL assisted turning of powder metallurgical manufactured Böhler K490 steel. *Sādhanā*, 47(3), 1-14.
- Bruschi, S., Tristo, G., Rysava, Z., Bariani, P. F., Umbrello, D., & De Chiffre, L. (2016). Environmentally clean micromilling of electron beam melted Ti6Al4V. *Journal of Cleaner Production*, 133, 932-941.
- Busch, K., Hochmuth, C., Pause, B., Stoll, A., & Wertheim, R. (2016). Investigation of cooling and lubrication strategies for machining high-temperature alloys. *Procedia CIRP*, 41, 835-840.
- Cai, C., Liang, X., An, Q., Tao, Z., Ming, W., & Chen, M. (2021). Cooling/lubrication performance of dry and supercritical CO₂-based minimum quantity lubrication in peripheral milling Ti-6Al-4V. *International Journal of Precision Engineering and Manufacturing-Green Technology*, 8(2), 405-421.
- Chegdani, F., & El Mansori, M. (2018). Friction scale effect in drilling natural fiber composites. *Tribology International*, 119, 622-630.

- Chen, J., Yu, W., Zuo, Z., Li, Y., Chen, D., An, Q., ... & Chen, M. (2021). Tribological properties and tool wear in milling of in-situ TiB₂/7075 Al composite under various cryogenic MQL conditions. *Tribology International*, *160*, 107021.
- Chen, W. H., Chiu, G. L., Ong, H. C., Lam, S. S., Lim, S., Ok, Y. S., & Kwon, E. E. (2021). Optimization and analysis of syngas production from methane and CO₂ via Taguchi approach, response surface methodology (RSM) and analysis of variance (ANOVA). *Fuel*, *296*, 120642.
- Dambhare, S., Deshmukh, S., Borade, A., Digalwar, A., & Phate, M. (2015). Sustainability issues in turning process: A study in Indian machining Industry. *Procedia CIRP*, *26*, 379-384.
- Danish, M., Ginta, T. L., Habib, K., Carou, D., Rani, A. M. A., & Saha, B. B. (2017). Thermal analysis during turning of AZ31 magnesium alloy under dry and cryogenic conditions. *The International Journal of Advanced Manufacturing Technology*, *91*(5), 2855-2868.
- Danish, M., Gupta, M. K., Rubaiee, S., Ahmed, A., & Korkmaz, M. E. (2021). Influence of hybrid Cryo-MQL lubri-cooling strategy on the machining and tribological characteristics of Inconel 718. *Tribology International*, *163*, 107178.
- Danish, M., Gupta, M. K., Rubaiee, S., Ahmed, A., Mahfouz, A., & Jamil, M. (2021). Machinability investigations on CFRP composites: A comparison between sustainable cooling conditions. *The International Journal of Advanced Manufacturing Technology*, *114*(11), 3201-3216.
- Debnath, S., Anwar, M., Pramanik, A., & Basak, A. K. (2021). Nanofluid-minimum quantity lubrication system in machining: towards clean manufacturing. In *Sustainable Manufacturing* (pp. 109-135). Elsevier.
- Deshpande, K. D. (2021). Identifying Important Features to Minimize Hole Deviation in Percussive Drilling.
- Deswal, S., Narang, R., & Chhabra, D. (2019). Modeling and parametric optimization of FDM 3D printing process using hybrid techniques for enhancing dimensional preciseness. *International Journal on Interactive Design and Manufacturing (IJIDeM)*, *13*(3), 1197-1214.

- Elsanabary, S. A., Elkaseer, A. I., Abd-Rabbo, S. M., Ali, M. A., & Abdou, S. M. I. (2021). Comparative Assessment of Different Optimization Techniques for Turning Operations. *MEJ. Mansoura Engineering Journal*, 40(5), 98-107.
- Eskandari, B., Bhowmick, S., & Alpas, A. T. (2022). Turning of Inconel 718 using liquid nitrogen: multi-objective optimization of cutting parameters using RSM. *The International Journal of Advanced Manufacturing Technology*, 120(5), 3077-3101.
- Faga, M. G., Priarone, P. C., Robiglio, M., Settineri, L., & Tebaldo, V. (2017). Technological and sustainability implications of dry, near-dry, and wet turning of Ti-6Al-4V alloy. *International Journal of Precision Engineering and Manufacturing-Green Technology*, 4(2), 129-139.
- Faraz, A., Biermann, D., & Weinert, K. (2009). Cutting edge rounding: An innovative tool wear criterion in drilling CFRP composite laminates. *International Journal of Machine Tools and Manufacture*, 49(15), 1185-1196.
- Fernández, D., Sandá, A., & Bengoetxea, I. (2019). Cryogenic milling: Study of the effect of CO₂ cooling on tool wear when machining Inconel 718, Grade EA1N Steel and Gamma TiAl. *Lubricants*, 7(1), 10.
- Field, M., & Merchant, M. E. (1949). Mechanics of formation of the discontinuous chip in metal cutting. *Transactions of the American Society of Mechanical Engineers*, 71(5), 421-428.
- Gaitonde, V. N., Karnik, S. R., Rubio, J. C. C., de Oliveira Leite, W., & Davim, J. P. (2014). Experimental studies on hole quality and machinability characteristics in drilling of unreinforced and reinforced polyamides. *Journal of Composite Materials*, 48(1), 21-36.
- Gajrani, K. K. (2020). Assessment of cryo-MQL environment for machining of Ti-6Al-4V. *Journal of Manufacturing Processes*, 60, 494-502.
- Gao, C., & Zhang, L. (2013). Effect of cutting conditions on the serrated chip formation in high-speed cutting. *Machining Science and Technology*, 17(1), 26-40.
- Gonsalves, J. A., Nayak, S. N., & Bolar, G. (2022). Experimental investigation on the performance of helical milling for hole processing in AZ31 magnesium

- alloy. *Journal of King Saud University-Engineering Sciences*, 34(5), 366-374.
- Gowthaman, B., Boopathy, S. R., & Kanagaraju, T. (2022). Effect of LN₂ and CO₂ Coolants in hard turning of AISI 4340 steel using tungsten carbide tool. *Surface Topography: Metrology and Properties*, 10(1), 015032.
- Grguraš, D., Sterle, L., & Pušavec, F. (2021). Cutting forces and chip morphology in LCO₂+ MQL assisted robotic drilling of Ti6Al4V. *Procedia CIRP*, 102, 299-302.
- Gupta, M. K., Boy, M., Korkmaz, M. E., Yaşar, N., Günay, M., & Krolczyk, G. M. (2022). Measurement and analysis of machining induced tribological characteristics in dual jet minimum quantity lubrication assisted turning of duplex stainless steel. *Measurement*, 187, 110353.
- Gupta, M. K., Niesłony, P., Sarikaya, M., Korkmaz, M. E., Kuntoğlu, M., Królczyk, G. M., & Jamil, M. (2022). Tool wear patterns and their promoting mechanisms in hybrid cooling assisted machining of titanium Ti-3Al-2.5 V/grade 9 alloy. *Tribology International*, 174, 107773.
- Gupta, M. K., Niesłony, P., Sarikaya, M., Korkmaz, M. E., Kuntoğlu, M., Krolczyk, G. M., & Jamil, M. (2022). Tool wear patterns and their promoting mechanisms in hybrid cooling assisted machining of titanium Ti-3Al-2.5 V/grade 9 alloy. *Tribology International*, 174, 107773.
- Gupta, M. K., Song, Q., et.al (2020). Ecological, economical and technological perspectives based sustainability assessment in hybrid-cooling assisted machining of Ti-6Al-4 V alloy. *Sustainable Materials and Technologies*, 26, e00218.
- Gupta, M. K., Song, Q., Liu, Z., Sarikaya, M., Jamil, M., Mia, M., ... & Krolczyk, G. M. (2021). Experimental characterisation of the performance of hybrid cryo-lubrication assisted turning of Ti-6Al-4V alloy. *Tribology International*, 153, 106582.
- Halim, N. A., Haron, C. C., Ghani, J. A., & Azhar, M. F. (2019). Response Surface Methodology (RSM) based analysis for tool life optimization in cryogenic CO₂ milling of Inconel 718. In *IOP Conference Series: Materials Science and Engineering* (Vol. 606, No. 1, p. 012015). IOP Publishing.

- Halim, N. H. A., Haron, C. H. C., Ghani, J. A., & Azhar, M. F. (2019). Tool wear and chip morphology in high-speed milling of hardened Inconel 718 under dry and cryogenic CO₂ conditions. *Wear*, *426*, 1683-1690.
- He, Y., Zhang, W., Li, Y. F., Wang, Y. L., Wang, Y., & Wang, S. L. (2021). An approach for surface roughness measurement of helical gears based on image segmentation of region of interest. *Measurement*, *183*, 109905.
- Hwang, C. L., Lai, Y. J., Liu, T. Y. (1993). A new approach for multiple objective decision making. *Computers and Operational Research*, *20*, pp. 889–899.
- International Molybdenum Associations (IMOA).
- Iqbal, A., Zaini, J., & Nauman, M. M. (2019). Machinability of Alloy Steel and Titanium Alloy under Carbon Dioxide Snow, Micro-lubrication and Hybrid Lubro-Cooling. In *IOP Conference Series: Materials Science and Engineering* (Vol. 521, No. 1, p. 012003). IOP Publishing.
- Isakson, S., Sadik, M. I., Malakizadi, A., & Krajnik, P. (2018). Effect of cryogenic cooling and tool wear on surface integrity of turned Ti-6Al-4V. *Procedia CIRP*, *71*, 254-259.
- Isakson, S., Sadik, M. I., Malakizadi, A., & Krajnik, P. (2018). Effect of cryogenic cooling and tool wear on surface integrity of turned Ti-6Al-4V. *Procedia CIRP*, *71*, 254-259.
- Jamil, M., Khan, A. M., et.al (2019). Effects of hybrid Al₂O₃-CNT nanofluids and cryogenic cooling on machining of Ti-6Al-4V. *The International Journal of Advanced Manufacturing Technology*, *102*(9), 3895-3909.
- Jebaraj, M., & Pradeep Kumar, M. (2019). Effect of cryogenic CO₂ and LN₂ coolants in milling of aluminum alloy. *Materials and Manufacturing Processes*, *34*(5), 511-520.
- Jebaraj, M., Kumar, P., & Anburaj, R. (2020). Effect of LN₂ and CO₂ coolants in milling of 55NiCrMoV7 steel. *Journal of Manufacturing Processes*, *53*, 318-327.
- Jebaraj, M., Pradeep Kumar, M., Yuvaraj, N., & Anburaj, R. (2020). Investigation of surface integrity in end milling of 55NiCrMoV7 die steel under the cryogenic environments. *Machining Science and Technology*, *24*(3), 465-488.

- Jerold, B. D., & Kumar, M. P. (2011). Experimental investigation of turning AISI 1045 steel using cryogenic carbon dioxide as the cutting fluid. *Journal of Manufacturing Processes*, 13(2), 113-119.
- Karim, M. R., Tariq, J. B., et.al (2021). Environmental, economical and technological analysis of MQL-assisted machining of Al-Mg-Zr alloy using PCD tool. *Sustainability*, 13(13), 7321.
- Kaynak, Y., &Gharibi, A. (2018). Progressive tool wear in cryogenic machining: the effect of liquid nitrogen and carbon dioxide. *Journal of Manufacturing and Materials Processing*, 2(2), 31.
- Kaynak, Y., &Gharibi, A. (2019). Cryogenic machining of titanium Ti-5553 alloy. *Journal of Manufacturing Science and Engineering*, 141(4).
- Khan, A. M., Anwar, S., Jamil, M., Nasr, M. M., Gupta, M. K., Saleh, et.al (2021). Energy, environmental, economic, and technological analysis of Al-GnP nanofluid-and cryogenic LN2-assisted sustainable machining of Ti-6Al-4V alloy. *Metals*, 11(1), 88.
- Khan, M. A. A., Hussain, M., Lodhi, S. K., Zazoum, B., Asad, M., & Afzal, A. (2022). Green Metalworking Fluids for Sustainable Machining Operations and Other Sustainable Systems: A Review. *Metals*, 12(9), 1466.
- Khanna, N., & Shah, P. (2020). Comparative analysis of dry, flood, MQL and cryogenic CO2 techniques during the machining of 15-5-PH SS alloy. *Tribology International*, 146, 106196.
- Khanna, N., Shah, P., Suri, N. M., Agrawal, C., Khatkar, S. K., Pusavec, F., &Sarıkaya, M. (2021). Application of environmentally-friendly cooling/lubrication strategies for turning magnesium/SiC MMCs. *Silicon*, 13(8), 2445-2459.
- Kilickap, E., Yardımeden, A., &HişmanÇelik, Y. (2017). Mathematical modelling and optimization of cutting force, tool wear and surface roughness by using artificial neural network and response surface methodology in milling of Ti-6242S. *Applied Sciences*, 7(10), 1064.
- Kim, D. M., Kim, D. Y., Banerjee, N., & Park, H. W. (2018). Predictive modeling for the cryogenic cooling condition of the hard turning process. *The*

-
- International Journal of Advanced Manufacturing Technology*, 99(9), 2877-2891.
- Kim, D. M., Kim, H. I., & Park, H. W. (2021). Tool wear, economic costs, and CO2 emissions analysis in cryogenic assisted hard-turning process of AISI 52100 steel. *Sustainable Materials and Technologies*, 30, e00349.
- Korkmaz, M. E., Gupta, M. K., Demirsöz, R., Boy, M., Yaşar, N., Günay, M., & Ross, N. S. (2022). On tribological characteristics of TiC rollers machined under hybrid lubrication/cooling conditions. *Tribology International*, 174, 107745.
- Korkmaz, M. E., Gupta, M. K., Demirsöz, R., Boy, M., Yaşar, N., Günay, M., & Ross, N. S. (2022). On tribological characteristics of TiC rollers machined under hybrid lubrication/cooling conditions. *Tribology International*, 174, 107745.
- Kumar, J., Verma, R. K., & Debnath, K. (2020). A new approach to control the delamination and thrust force during drilling of polymer nanocomposites reinforced by graphene oxide/carbon fiber. *Composite Structures*, 253, 112786.
- Laouissi, A., Yaltese, M. A., Belbah, A., Belhadi, S., & Haddad, A. (2019). Investigation, modeling, and optimization of cutting parameters in turning of gray cast iron using coated and uncoated silicon nitride ceramic tools. Based on ANN, RSM, and GA optimization. *The International Journal of Advanced Manufacturing Technology*, 101(1), 523-548.
- Lee, H. W., & Kwon, W. T. (2010). Determination of the minute range for RSM to select the optimum cutting conditions during turning on CNC lathe. *Journal of mechanical science and technology*, 24(8), 1637-1645.
- Li, K., Yan, S., Zhong, Y., Pan, W., & Zhao, G. (2019). Multi-objective optimization of the fiber-reinforced composite injection molding process using Taguchi method, RSM, and NSGA-II. *Simulation modelling practice and theory*, 91, 69-82.
- Liu, C., Wan, M., Zhang, W., & Yang, Y. (2021). Chip formation mechanism of Inconel 718: a review of models and approaches. *Chinese Journal of Mechanical Engineering*, 34, 1-16.

- Mahalil, K., Abd Rahim, E., & Mohid, Z. (2019). Performance Evaluation Of Sustainable Coolant Techniques On Burnishing Process. In *IOP Conference Series: Materials Science and Engineering* (Vol. 494, No. 1, p. 012001). IOP Publishing.
- Makhesana, M. A., Patel, K. M., & Bagga, P. J. (2022). Evaluation of Surface Roughness, Tool Wear and Chip Morphology during Machining of Nickel-Based Alloy under Sustainable Hybrid Nanofluid-MQL Strategy. *Lubricants*, *10*(11), 315.
- Manimaran, G., Anwar, S., Rahman, M. A., Korkmaz, M. E., Gupta, M. K., Alfaify, A., & Mia, M. (2021). Investigation of surface modification and tool wear on milling Nimonic 80A under hybrid lubrication. *Tribology International*, *155*, 106762.
- Mia, M., Khan, M. A., & Dhar, N. R. (2017). Study of surface roughness and cutting forces using ANN, RSM, and ANOVA in turning of Ti-6Al-4V under cryogenic jets applied at flank and rake faces of coated WC tool. *The International Journal of Advanced Manufacturing Technology*, *93*(1), 975-991.
- Misumi Industry India.
- Mondal, N., Mandal, S., & Mandal, M. C. (2020). FPA based optimization of drilling burr using regression analysis and ANN model. *Measurement*, *152*, 107327.
- Muhamad, S. S., Ghani, J. A., Haron, C. H. C., & Yazid, H. (2019). Investigation of cutting forces in end milling of AISI 4340 under dry and cryogenic conditions. *Jurnal Tribologi*, *23*, 125-136.
- NimelSworna Ross, K., & Manimaran, G. (2019). Effect of cryogenic coolant on machinability of difficult-to-machine Ni-Cr alloy using PVD-TiAlN coated WC tool. *Journal of the Brazilian Society of Mechanical Sciences and Engineering*, *41*(1), 1-14.
- Ortiz-de-Zarate, G., Soriano, D., Madariaga, A., Garay, A., Rodriguez, I., & Arrazola, P. J. (2021). Experimental and FEM analysis of dry and cryogenic turning of hardened steel 100Cr6 using CBN Wiper tools. *Procedia CIRP*, *102*, 7-12.

- Patel, T., Khanna, N., Yadav, S., Shah, P., Sarikaya, M., et.al (2021). Machinability analysis of nickel-based superalloy Nimonic 90: a comparison between wet and LCO₂ as a cryogenic coolant. *The International Journal of Advanced Manufacturing Technology*, 113(11), 3613-3628.
- Pereira, O., Celaya, A., Urbikaín, G., Rodríguez, A., Fernández-Valdivielso, A., & de Lacalle, L. N. L. (2020). CO₂ cryogenic milling of Inconel 718: cutting forces and tool wear. *Journal of Materials Research and Technology*, 9(4), 8459-8468.
- Pereira, O., Rodríguez, A., Ayesta, I., García, J. B., Fernández-Abia, A. I., & Lacalle, L. N. L. D. (2016). A cryo lubri-coolant approach for finish milling of aeronautical hard-to-cut materials. *International Journal of Mechatronics and Manufacturing Systems*, 9(4), 370-384.
- Pusavec, F., Deshpande, A., Yang, S., M'Saoubi, R., Kopac, J., Dillon Jr, O. W., & Jawahir, I. S. (2014). Sustainable machining of high temperature Nickel alloy–Inconel 718: part 1–predictive performance models. *Journal of Cleaner Production*, 81, 255-269.
- Pušavec, F., Grguraš, D., Koch, M., & Krajnik, P. (2019). Cooling capability of liquid nitrogen and carbon dioxide in cryogenic milling. *CIRP Annals*, 68(1), 73-76.
- Rahim, E. A., Rahim, A. A., Ibrahim, M. R., & Mohid, Z. (2016). Experimental investigation of supercritical carbon dioxide (SCCO₂) performance as a sustainable cooling technique. *Procedia Cirp*, 40, 637-641.
- Rodriguez, I., Soriano, D., Ortiz-de-Zarate, G., Cuesta, M., Pušavec, F., & Arrazola, P. J. (2022). Effect of Tool Geometry and LCO₂ Cooling on Cutting Forces and Delamination when Drilling CFRP Composites Using PCD Tools. *Procedia CIRP*, 108, 752-757.
- Rooki, R., Ardejani, F. D., Moradzadeh, A., Mirzaei, H., Kelessidis, V., Maglione, R., & Norouzi, M. (2012). Optimal determination of rheological parameters for herschel-bulkley drilling fluids using genetic algorithms (GAs). *Korea-Australia Rheology Journal*, 24, 163-170.
- Ross, N. S., Srinivasan, N., Amutha, P., Gupta, M. K., & Korkmaz, M. E. (2022). Thermo-physical, tribological and machining characteristics of Hastelloy

- C276 under sustainable cooling/lubrication conditions. *Journal Of Manufacturing Processes*, 80, 397-413.
- Salur, E. (2022). Understandings the tribological mechanism of Inconel 718 alloy machined under different cooling/lubrication conditions. *Tribology International*, 107677.
- Sanchez, J. A., Pombo, I., Alberdi, R., Izquierdo, B., Ortega, N., Plaza, S., & Martinez-Toledano, J. (2010). Machining evaluation of a hybrid MQL-CO2 grinding technology. *Journal of Cleaner Production*, 18(18), 1840-1849.
- Santhosh, A. J., Tura, A. D., Jiregna, I. T., Gemechu, W. F., Ashok, N., & Ponnusamy, M. (2021). Optimization of CNC turning parameters using face centred CCD approach in RSM and ANN-genetic algorithm for AISI 4340 alloy steel. *Results in Engineering*, 11, 100251.
- Saravanakumar, A., Sasikumar, P., & Nilavusri, N. (2016). Optimization of machining parameters using taguchi method for surface roughness. *J. Mater. Environ. Sci*, 7(5), 1556-1561.
- Sartori, S., Ghiotti, A., & Bruschi, S. (2017). Hybrid lubricating/cooling strategies to reduce the tool wear in finishing turning of difficult-to-cut alloys. *Wear*, 376, 107-114.
- Sen, B., Hussain, S. A. I., Gupta, M. K., Mia, M., & Mandal, U. K. (2021). Swarm intelligence based selection of optimal end-milling parameters under minimum quantity nano-green lubricating environment. *Proceedings of the Institution of Mechanical Engineers, Part C: Journal of Mechanical Engineering Science*, 235(23), 6969-6983.
- Senthil Kumar, A., Rahman, M., & Ng, S. L. (2002). Effect of high-pressure coolant on machining performance. *The International Journal of Advanced Manufacturing Technology*, 20, 83-91.
- Shah, P., & Khanna, N. (2020). Comprehensive machining analysis to establish cryogenic LN2 and LCO2 as sustainable cooling and lubrication techniques. *Tribology International*, 148, 106314.
- Shah, P., Bhat, P., & Khanna, N. (2021). Life cycle assessment of drilling Inconel 718 using cryogenic cutting fluids while considering sustainability parameters. *Sustainable Energy Technologies and Assessments*, 43, 100950.

- Shah, P., Khanna, N., Maruda, R. W., Gupta, M. K., & Krolczyk, G. M. (2021). Life cycle assessment to establish sustainable cutting fluid strategy for drilling Ti-6Al-4V. *Sustainable Materials and Technologies*, 30, e00337.
- Shah, P., Khanna, N., Singla, A. K., & Bansal, A. (2021). Tool wear, hole quality, power consumption and chip morphology analysis for drilling Ti-6Al-4V using LN₂ and LCO₂. *Tribology International*, 163, 107190.
- Sharma, A., Sharma, N., Singh, R. P., Arora, R., Gill, R. S., & Singh, G. (2022). Micro-drill on Al/SiC composite by EDD process: An RSM-MOGOA based hybrid approach. *International Journal of Lightweight Materials and Manufacture*, 5(4), 564-575.
- Sivaraman, V., & Prakash, S. (2019). Performance and evaluation of MoS₂ based machining using PVD-TiAlN coated tool. *Journal of Mechanical Science and Technology*, 33(9), 4383-4388.
- Srivastav, R. K., Sudheer, K. P., & Chaubey, I. (2007). A simplified approach to quantifying predictive and parametric uncertainty in artificial neural network hydrologic models. *Water Resources Research*, 43(10).
- Sterle, L., Krajnik, P., & Pušavec, F. (2021). The effects of liquid-CO₂ cooling, MQL and cutting parameters on drilling performance. *CIRP Annals*, 70(1), 79-82.
- Sulaiman, S., Roshan, A., & Borazjani, S. (2014). Effect of cutting parameters on tool-chip interface temperature in an orthogonal turning process. In *Advanced Materials Research* (Vol. 903, pp. 21-26). Trans Tech Publications Ltd, Australia.
- Vankanti, V. K., & Ganta, V. (2014). Optimization of process parameters in drilling of GFRP composite using Taguchi method. *Journal of Materials Research and Technology*, 3(1), 35-41.
- Venkata Rao, K., & Murthy, P. B. G. S. N. (2018). Modeling and optimization of tool vibration and surface roughness in boring of steel using RSM, ANN and SVM. *Journal of intelligent manufacturing*, 29(7), 1533-1543.
- Vishal, R., Gnanavel, B. K., Manimaran, G., & Ross, K. N. S. (2018). *Impact on machining of AISI H13 steel using coated carbide tool under vegetable oil minimum quantity lubrication*. ASTM International.

- Wang, T.C., and Chang, T.H. (2007). Application of TOPSIS in evaluating initial training aircraft under a fuzzy environment. *Expert Systems with Applications*. 33(4) 870-880 (2007).
- Wang, Y. X., Wang, H. X., & Tian, H. H. (2022). Cylindricity Error Measurement and Evaluation Based on Step Acceleration Algorithm in Crankshaft Measuring Machine. *MAPAN*, 1-10.
- Wang, Z., Kovvuri, V., Araujo, A., Bacci, M., Hung, W. N. P., & Bukkapatnam, S. T. S. (2016). Built-up-edge effects on surface deterioration in micromilling processes. *Journal of Manufacturing Processes*, 24, 321-327.
- Wohlfeil, F. (2015). Radical Technological Innovation: Case Study of Cryogenic Machining by SME.
- Wu, J., Jiang, Z., Wan, L., Song, H., & Abbass, K. (2021). Robust Optimization for Precision Product using Taguchi-RSM and Desirability Function. *Arabian Journal for Science and Engineering*, 46(3), 2803-2814.
- Zerti, A., Yallese, M. A., Zerti, O., Nouioua, M., & Khettabi, R. (2019). Prediction of machining performance using RSM and ANN models in hard turning of martensitic stainless steel AISI 420. *Proceedings of the Institution of Mechanical Engineers, Part C: Journal of Mechanical Engineering Science*, 233(13), 4439-4462.